

Certificate of Registration

Certificate Number 083

Placed on the Market under the Name of

**Beamfast Limited T/A Secure Fire Doors and T/A Security Fire
Doors**

**Units F, H & I, Forest Industrial Park
Forest Road
Hainault
Essex
IG6 3HL
United Kingdom**

and produced in the manufacturing plant

**Beamfast Limited T/A Secure Fire Doors and T/A Security Fire Doors, Unit F, H & I Forest
Industrial Park, Forest Road, Hainault, Essex, IG6 3HL, United Kingdom**

This certificate attests that all provisions have been met concerning the BM TRADA requirements of the scheme:

Q-Mark Timber Fire Door Manufacture



Date of Initial Certification: **09/11/2005**

Date of Last Issue: **12/12/2025**

Date of Expiry: **11/04/2026**

**Natasha Bambridge
(Divisional Director)**
For and on behalf of Element

Scope of Certification

Primary Field of Application (FoA) Reports (owned by this certified company)

Either used in isolation, or can be used in conjunction with an appropriate associated document for this company, providing that the FoA report allows it and that both documents are compatible with each other. Where more than one primary FoA is listed for the same doorset type, they cannot be mix and matched, only one FoA is to be chosen and followed precisely

| Type | FoA Report | Re v | Owned by Certified Company named on this scope | Doorset Description | Integrity Period | FoA Standard |
|-------|------------|------|--|---------------------|------------------|--------------|
| Fire | - | - | - | - | - | - |
| Smoke | - | - | - | - | - | - |
| Fire | - | - | - | - | - | - |
| Smoke | - | - | - | - | - | - |

Primary Field of Application (FoA) Reports (owned by and cascaded by a System Supplier)

The revision status of each FoA can be verified on the BM TRADA website under each System Supplier's certification entry. They are either used in isolation, or can be used in conjunction with an appropriate associated document for this company, providing that the FoA report allows it and that both documents are compatible with each other. Where more than one primary FoA is listed for the same doorset type, they cannot be mix and matched, only one FoA is to be chosen and followed precisely.

| Type | FoA Report | System Supplier owner of Assessment Report | Doorset Description | Integrity Period | FoA Standard |
|-------|--------------|--|---|------------------|--------------|
| Fire | FEA/F98164 | Pacific Rim Wood Ltd | Flamebreak Doorsets for 30 minutes Fire Resistance (Glazed or Unglazed) | 30min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | FEA/F02141 | Pacific Rim Wood Ltd | Flamebreak 660 and FF660 Doorsets for 60 minutes Fire Resistance (Glazed or Unglazed) | 60min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | Chilt/A01204 | Halspan Limited | Optima 30 Part 1 Timber (Glazed or Unglazed) | 30min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | Chilt/A01205 | Halspan Limited | Optima 60 Part 1 Timber (Glazed or Unglazed) | 60min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | FEA/F97174 | Halspan Limited | Prima 30 Part 1 Timber (Glazed or Unglazed) | 30min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | FEA/F96103 | Halspan Limited | Prima 60 Part 1 Timber (Glazed or Unglazed) | 60min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | WF407090 | Falcon Timber Limited | STREbord® 44 doorsets for 30 Minutes Fire Resistance (Front Entrance Doorsets) (Glazed or Unglazed) | 30min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | WF407090 | Falcon Timber Limited | STREbord® 54 doorsets for 30 Minutes Fire Resistance (Front Entrance Doorsets) (Glazed or Unglazed) | 30min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | WF407090 | Falcon Timber Limited | STREdor® 44 doorsets for 30 Minutes Fire Resistance (Front Entrance Doorsets) (Glazed or Unglazed) | 30min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | WF407090 | Falcon Timber Limited | STREdor® 54 doorsets for 30 Minutes Fire Resistance (Front Entrance Doorsets) (Glazed or Unglazed) | 30min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |

| | | | | | |
|-------|-----------------|-----------------------|--|-------|-------------|
| Fire | WF427764 | Falcon Timber Limited | STREbord® 54 Fire Resisting Doorsets for 60 minutes fire resistance (Front Entrance Doorsets) (Glazed or Unglazed) | 60min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | WF427764 | Falcon Timber Limited | STREdor® 54 Fire Resisting Doorsets for 60 minutes fire resistance (Front Entrance Doorsets) (Glazed or Unglazed) | 60min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | Chilt/A02066 | Falcon Timber Limited | STREbord® 44 door assemblies for 30 Minutes Fire Resistance (Glazed or Unglazed) | 30min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | Chilt/A02067 | Falcon Timber Limited | STREbord® 54 doorsets for 60 Minutes Fire Resistance (Glazed or Unglazed) | 60min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | BMT/CNA/F151 59 | Falcon Timber Limited | STREdor® 44 doorsets for 30 Minutes Fire Resistance (Glazed or Unglazed) | 30min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |
| Fire | WF377027 | Falcon Timber Limited | STREdor® 54 Doorsets for 60 Minutes Fire Resistance (Glazed or Unglazed) | 60min | BS 476 Pt22 |
| Smoke | N/A | - | | | N/A |

Test Reports

Test reports cannot be used in conjunction with any primary FoA reports, other test reports or associated documents. They must be followed precisely without any deviation whatsoever.

No specification or parameter changes are allowed at all from that stated within the test report such as size, shape, design, glazing, leaf/frame specification, hardware etc.

| Type | Test Report | Owner of Test Report | Doorset Description | Integrity Period | Test Standard |
|-----------|-------------|----------------------|---------------------|------------------|---------------|
| Fire only | - | - | - | - | - |